

HONSHU
AIR CONDITIONER

THE SMART CHOICE



(Energy Efficiency Rating)



**BETTER COOL
GO GREEN**



LED



Easy Cleaning



Quiet Operation



Anion



Auto Restart



Anti-Corrosion



www.honshu.co.id

Technical Specification



Model No.		LOW WATT			HSD12006	HSD18006	HSD23006		
		HSD6006	HSD7006	HSD9006					
		★★★★★	★★★★★	★★★★★	★★★★★	★★★★★	★★★★★		
Control type		Remote							
Rated cooling capacity	Btu/h;	5000	7000	9000	12000	18000	23000		
EER for cooling		12.41	10.19	11.01	10.07	10.06	10.06		
Indoor noise level	Hi/Med/Lo	dB(A)		36/34/33	38/37/36	38/37/36	39/38/37	45/43/42	42/38/37
Outdoor noise level		dB(A)		50	50	50	52	52	53
Electrical Data									
Power supply		220-240V~/50Hz/1P							
Voltage Range	V	187~253	187~253	184~264	198~242	198~242	198~264		
Rated current	Cooling	A	1.45	2.80	3.00	5.50	6.8	12.0	
Rated input	Cooling	W	320	600	660	1210	1496	2640	
Max Current	Cooling	A	1.90	3.80	4.00	8.83	13.1	18.20	
Max Power input	Cooling	W	420	825	860	1904	2500	3809	
Refrigerating System									
Refrigerant/Charge	Gram	R410A /410g	R410A /400g	R410A /410g	R410A /650g	R410A/960g	R410A /1380g		
Connections									
Connecting Pipe	Gas	Inches	3/8"	3/8"	3/8"	1/2"	1/2"	"5/8"	
	Liquid	Inches	1/4"	1/4"	1/4"	1/4"	1/4"	"3/8"	
Others									
Suitable area		m ²	5~9	9~12	12~16	16~23	23~35	35~50	
Net dimensions (W x H x D)	Indoor	mm	705x240x180	705x240x180	766x240x185	770x240x180	900x280x205	900x280x202	
	Outdoor	mm	600x500x232	600x500x232	600x500x232	700x552x256	820x605x300	902x650x307	
Net weight	Indoor	kg	6.5	8	8	8	11	11	
	Outdoor	kg	20	21	21	29	35	50	
Packing dimensions (W x H x D)	Indoor	mm	805x305x255	855x305x255	855x305x255	855x305x255	995x365x298	995x365x298	
	Outdoor	mm	705x300x550	705x300x550	705x300x550	803x325x585	930x640x380	1037x705x433	
Gross weight	Indoor	kg	8	10	10	10	14	14	
	Outdoor	kg	24	27	27	34	41	57	

HONSHU
AIR CONDITIONER

THE SMART CHOICE

www.honshu.co.id